

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 August 2005 (18.08.2005)

PCT

(10) International Publication Number
WO 2005/076329 A1

(51) International Patent Classification⁷: **H01L 21/265**,
H01J 37/04, 37/317, H01L 21/20

(74) Agent: **OKUDA, Seiji**; OKUDA & ASSOCIATES, 10th
Floor, Osaka Securities Exchange Bldg., 8-16, Kitahama
1-chome, Chuo-ku, Osaka-shi, Osaka 541-0041 (JP).

(21) International Application Number:
PCT/JP2005/001740

(22) International Filing Date: 1 February 2005 (01.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-026668 3 February 2004 (03.02.2004) JP

(71) Applicant (for all designated States except US): **SHARP
KABUSHIKI KAISHA** [JP/JP]; 22-22, Nagaike-cho,
Abeno-ku, Osaka-shi, Osaka, 5458522 (JP).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **NAKANISHI, Ken**
[JP/JP]; 65-1-307, Eiwachō, Kashihara-shi, Nara, 6340046
(JP).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ION DOPING APPARATUS, ION DOPING METHOD, SEMICONDUCTOR DEVICE, AND METHOD OF FABRICATING SEMICONDUCTOR DEVICE



(57) Abstract: An ion doping apparatus includes: a chamber 11; a discharge section 13 for discharging a gaseous content from within the chamber 11; an ion source 12 being provided in the chamber 11 and including an inlet 14 through which to introduce a gas containing an element to be used for doping, the ion source 12 decomposing the gas introduced through the inlet 14 to generate ions containing the element to be used for doping; an acceleration section 23 for pulling out from the ion source 12 the ions generated at the ion source 12 and accelerating the ions toward a target object held in the chamber; and a beam current meter 26 for measuring a beam current caused by the accelerated ions. The beam current is measured by the beam current meter 26 a plurality of times, and if a result of the measurements indicates a stability of the beam current, the ion doping apparatus automatically begins to implant into the target object the ions containing the element to be used for doping. Thus, an ion doping apparatus having excellent doping amount controllability is provided.

**Published:**

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.